

1MT34 Piston Actuator

The 1MT34 Piston Actuator is a pyrotechnic-actuated device that produces linear motion.



Its compact size, light weight, high reliability and environmental resistance make it ideal for aerospace and ordnance applications.


Characteristics

Some of the characteristics listed here are nominal; others are levels to which the units have been tested. There are no limits on design capabilities. Please consult an EaglePicher representative before using this data as a specification.


	Specifications		
	Electrical		
	Bridge Resistance @ 70°F (21°C)	1.0 ± 0.1 ohm	
	All-Fire Current	5 amp pulse, 10 ms (see graph)	
	No-Fire Current @ 225°F (107°C)	1 amp - 1 watt, 5 min	
-	Insulation Resistance	1megohm minimum @ 500 Vdc	
	Static Resistance	25,000 V discharge from a 500 pF capacitor through a 5000 ohm series resistor	
	Mechanical		
	Size	See drawing	
	Weight	2.0 gm Max.	
	Seal	Hermetically sealed by a glass-to- metal seal electrical feed-thru and solder seals at each end	
	Piston Motor	Stroke: 1/4" (6.35 mm) Force (air bellows): 20 lbs min. throughout the entire stroke. Force (peak): 200 lbs min. (zero displacement)	
	Function Time	10 ms Max. with 5.0 amp firing current	

Specifications Continued		
Environmental		
Temperature	Operating range: -65° to +160°F (-54° to +71°C)	
Storage	-80° to +255°F (-62° to +107°C) (limited time hot)	
Shock	1/2 sine wave pulse of 200 g's Min. for 1.5 ms and 65 g's Min. for 9 ms	
Vibration	MIL-STD-810, Table 514-1 Aircraft Category, Procedure 1, Parts 1, 2 & 3, Curve H. Each resonant and cycling period divided equally among -65°, +70°, and +200°F (-54°, +21°, and +93°C)	
Temperature Shock/Humidity/ Altitude	MIL-I-23659	
Chemical		
Ignition Compound	Barium Styphnate	
Freight Classification		
Shipping Name	Release Devices, Explosive	
Identification Number	UN0173	
Hazard Classification	1.4S	

PO Box 47 | Joplin, Missouri 64802-0047 USA | tel 417.623.8000 | fax 417.623.0850 | **www.eaglepicher.com**



DIMENSIONS IN PARENTHESIS () ARE IN MM.





EaglePicher Technologies, LLC

PO Box 47, Joplin, Missouri 64802-0047, USA tel 417.623.8000 | fax 417.623.0850 www.eaglepicher.com