# EaglePicher™ Technologies, LLC A WECTRA\ Company

# Dual Mode 15V/30V Primary Battery



Non-Rechargeable Li/CF<sub>x</sub>-MnO<sub>2</sub> Hybrid

Highly reliable, lightweight battery, with 2X the capacity of Li-SO<sub>2</sub> and impressive rate capability over a wide temperature range

#### **Features & Benefits**


- 2X the capacity of Li-SO, BA-5590 Battery
- 1.4X the capacity of Li-MnO<sub>2</sub> BA-5390 Battery
- → Capable of operating in 15V or 30V modes
- ★ Excellent rate capability
- + Patented contour case design for improved heat dissipation
- → Wide operating temperature range
- + Current and thermal fuses for safe operation
- Long shelf life
- Wide range of mission applications
- State of Charge Indicator (5 levels)
- Complete Discharge Device
- SMBus interface capability


### **Applications**


- Meets BA-5790 requirements
- Alternative to BA-5590 and BA-5390 batteries
- Soldier power: C4ISR, Silent watch
- Unattended ground sensors
- Survival and emergency equipment
- GPS/Mobile assist devices
- Alarming devices


<b>Specifications</b>			
Part Number	LCF-15002	LCF-15002	
	30V Mode	15V Mode	
Nominal Voltage	26.0 Volts*	13.0 Volts*	
Maximum Voltage	33.0 Volts	16.5 Volts	
Minimum Voltage (cut-off)	20.0 Volts	10.0 Volts	
Capacity	15.0 Ah*	30.0 Ah*	
Max Continuous Current	2A	4A	
Max Pulse Current	2.5A	5.0A	
Weight	1010 g	1010 g	
Specific Energy	386 Wh/kg	386 Wh/kg	
Energy Density	446 Wh/l	446 Wh/l	
Operating Temperature	-40°C to +60°C	-40°C to +60°C	
Storage Temperature	-40°C to +71°C	-40°C to +71°C	
Exterior	Hard plastic case	Hard plastic case	
Terminals / Connector	Connector SC-C-1	Connector SC-C-179492	
Transportation	Class 9 - U.S. and	Class 9 - U.S. and International**	
*At 21°C, 2.0 Amp Load per battery section ** Contact EaglePicher for complete transp	9		


## LCF-15002











EaglePicher™
Technologies, LLC

A VECTRA Company



#### **EaglePicher Technologies, LLC**

PO Box 47, Joplin, Missouri 64802-0047, USA tel 417.623.8000 | fax 417.623.0850 www.eaglepicher.com

This information is released to the public domain in accordance with ITAR 22 CFR 120.11.